







DC INDUCTIVE PROXIMITY SWITCH(M18)

Diameter	M18		M18	
Shielded/non-Shielded	Shielded/ Non-Shielded		Shielded/ Non-Shielded	
Switching Distance Sn mm	5mm / 8mm		5mm / 8mm	
Housing Material	stainless steel or nickel plated brass		stainless steel or nickel plated brass	
With LED/Without LED	With LED		With LED	
Picture				
Operating Voltage	10-30VDC / 5-36VDC / 10-55V/ 10-60VDC		10-30VDC / 5-36VDC / 10-55V/ 10-60VDC	
Ripple	<10%		<10%	
No Load Current	<10mA		<10mA	
Max. Load Current	200mA		200mA	
Leakage Current	<0.01mA		<0.01mA	
Voltage Drop	<1.5V		<1.5V	
Switching Frequency	1KHZ / 500HZ		1KHZ / 500HZ	
Response Time	0.2ms/0.2ms 0.5ms/0.5ms		0.2ms/0.2ms 0.5ms/0.5ms	
Switching Hysteresis	<15%(Sr)		<15%(Sr)	
Repeat Accuracy	<1.0%(Sr)		<1.0%(Sr)	
Protection Category	IP67		IP67	
Operating Temperature	-25 °C - +70 °C		-25 °C - +70 °C	
Temperature Drift	<10%(Sr)		<10%(Sr)	
Short Circuit Protection	YES		YES	
Overload Trip Point	220MA		220MA	
Material Active Face	POM/PBT		POM/PBT	
DC 3 wire 10-30V NPN N.O.	D1B1-M1805N-O3A2 ; D1B2-M1808N-O3A2	1	D1B1-M1805N-O3S2 ; D1B2-M1808N-O3S2	1
DC 3 wire 10-30V NPN N.C.	D1B1-M1805N-C3A2 ; D1B2-M1808N-C3A2	2	D1B1-M1805N-C3S2 ; D1B2-M1808N-C3S2	2
DC 3 wire 10-30V PNP N.O.	D1B1-M1805P-O3A2 ; D1B2-M1808P-O3A2	3	D1B1-M1805P-O3S2 ; D1B2-M1808P-O3S2	3
DC 3 wire 10-30V PNP N.C.	D1B1-M1805P-C3A2 ; D1B2-M1808P-C3A2	4	D1B1-M1805P-C3S2 ; D1B2-M1808P-C3S2	4
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)	D1B1-M1805P-S4A2 ; D1B2-M1808P-S4A2	6	D1B1-M1805P-S4S2 ; D1B2-M1808P-S4S2	6
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)	D1B1-M1805N-S4A2 ; D1B2-M1808N-S4A2	5	D1B1-M1805N-S4S2 ; D1B2-M1808N-S4S2	5
DC 2 wire 10-60V N.O.	D4B1-M1808C-O2A2 ; D4B2-M1808C-O2A2	7	D4B1-M1808C-O2S2 ; D4B2-M1808C-O2S2	7
DC 2 wire 10-60V N.C.	D4B1-M1805C-C2A2 ; D4B2-M1808C-C2A2	8	D4B1-M1805C-C2S2 ; D4B2-M1808C-C2S2	8
DC 3 wire 10-55v NPN N.O.	D3B1-M1805N-O3A2 ; D3B2-M1808N-O3A2	1	D3B1-M1805N-O3S2 ; D3B2-M1808N-O3S2	1
DC 3 wire 10-55v NPN N.C.	D3B1-M1805N-C3A2 ; D3B2-M1808N-C3A2	2	D3B1-M1805N-C3S2 ; D3B2-M1808N-C3S2	2
DC 3 wire 10-55v PNP N.O.	D3B1-M1805P-O3A2 ; D3B2-M1808P-O3A2	3	D3B1-M1805P-O3S2 ; D3B2-M1808P-O3S2	3
DC 3 wire 10-55v PNP N.C.	D3B1-M1805P-C3A2 ; D3B2-M1808P-C3A2	4	D3B1-M1805P-C3S2 ; D3B2-M1808P-C3S2	4
DC 3 wire 5-36V PNP N.C.	D2B1-M1805N-O3A2 ; D2B2-M1808N-O3A2	1	D2B1-M1805N-O3S2 ; D2B2-M1808N-O3S2	1
DC 3 wire 5-36V PNP N.O.	D2B1-M1805N-C3A2 ; D2B2-M1808N-C3A2	2	D2B1-M1805N-C3S2 ; D2B2-M1808N-C3S2	2
DC 3 wire 5-36V NPN N.C.	D2B1-M1805P-O3A2 ; D2B2-M1808P-O3A2	3	D2B1-M1805P-O3S2 ; D2B2-M1808P-O3S2	3
DC 3 wire 5-36V NPN N.O.	D2B1-M1805P-C3A2 ; D2B2-M1808P-C3A2	4	D2B1-M1805P-C3S2 ; D2B2-M1808P-C3S2	4
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)	D2B1-M1805P-S4A2 ; D2B2-M1808P-S4A2	6	D2B1-M1805P-S4S2 ; D2B2-M1808P-S4S2	6
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)	D2B1-M1805N-S4A2 ; D2B2-M1808N-S4A2	5	D2B1-M1805N-S4S2 ; D2B2-M1808N-S4S2	5
Wiring diagram number				
Dimensions (unit: mm)				
Cable 2M (PVC)	5.8φ3x0.15 or 5.8φ4x0.15		4φ3x.0.34 or 4φ4x0.34	
Weight	approx.153g / approx.144g		approx.132g / approx.134g	

Subject to modifications without notice

Tel: +86-755-2646 7962

Fax: +86-755-2646 7925

MSN: dfan852@hotmail.com

Web: www.mountiger.com

E-mail: sales@mountiger.com

QQ: 873764592

