






DC INDUCTIVE PROXIMITY SWITCH(M18)

Diameter	M18			M18		
Shielded/non-Shielded	Shielded/ Non-Shielded			Shielded/ Non-Shielded		
Switching Distance Sn mm	8mm / 16mm			8mm / 16mm		
Housing Material	stainless steel or nickel plated brass			stainless steel or nickel plated brass		
With LED/Without LED	With LED			With LED		
Picture						
Operating Voltage	10-30VDC / 5-36VDC / 10-55V/ 10-60VDC			10-30VDC / 5-36VDC / 10-55V/ 10-60VDC		
Ripple	<10%			<10%		
No Load Current	<10mA			<10mA		
Max. Load Current	200mA			200mA		
Leakage Current	<0.01mA			<0.01mA		
Voltage Drop	< 2.0V			< 2.0V		
Switching Frequency	500HZ / 150HZ			500HZ / 150HZ		
Response Time	0.5ms/0.5ms 1ms / 1ms			0.5ms/0.5ms 1ms / 1ms		
Switching Hysteresis	<15%(Sr)			<15%(Sr)		
Repeat Accuracy	<1.0%(Sr)			<1.0%(Sr)		
Protection Category	IP67			IP67		
Operating Temperature	-25 °C - +70 °C			-25 °C - +70 °C		
Temperature Drift	<10%(Sr)			<10%(Sr)		
Short Circuit Protection	YES			YES		
Overload Trip Point	220MA			220MA		
Material Active Face	POM/PBT			POM/PBT		
DC 3 wire 10-30V NPN N.O.	D1B1-M1808N-O3A2	D1B2-M1816N-O3A2	1	D1B1-M1808N-O3S2	D1B2-M1816N-O3S2	1
DC 3 wire 10-30V NPN N.C.	D1B1-M1808N-C3A2	D1B2-M1816N-C3A2	2	D1B1-M1808N-C3S2	D1B2-M1816N-C3S2	2
DC 3 wire 10-30V PNP N.O.	D1B1-M1808P-O3A2	D1B2-M1816P-O3A2	3	D1B1-M1808P-O3S2	D1B2-M1816P-O3S2	3
DC 3 wire 10-30V PNP N.C.	D1B1-M1808P-C3A2	D1B2-M1816P-C3A2	4	D1B1-M1808P-C3S2	D1B2-M1816P-C3S2	4
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)	D1B1-M1808P-S4A2	D1B2-M1816P-S4A2	6	D1B1-M1808P-S4S2	D1B2-M1816P-S4S2	6
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)	D1B1-M1808N-S4A2	D1B2-M1816N-S4A2	5	D1B1-M1808N-S4S2	D1B2-M1816N-S4S2	5
DC 2 wire 10-60V N.O.	D4B1-M1808C-O2A2	D4B2-M1816C-C2A2	7	D4B1-M1808C-O2S2	D4B2-M1816C-O2S2	7
DC 2 wire 10-60V N.C.	D4B1-M1808C-C2A2	D4B2-M1816C-O2A2	8	D4B1-M1808C-C2S2	D4B2-M1816C-C2S2	8
DC 3 wire 10-55v NPN N.O.	D3B1-M1808N-O3A2	D3B2-M1816N-O3A2	1	D3B1-M1808N-O3S2	D3B2-M1816N-O3S2	1
DC 3 wire 10-55v NPN N.C.	D3B1-M1808N-C3A2	D3B2-M1816N-C3A2	2	D3B1-M1808N-C3S2	D3B2-M1816N-C3S2	2
DC 3 wire 10-55v PNP N.O.	D3B1-M1808P-O3A2	D3B2-M1816P-O3A2	3	D3B1-M1808P-O3S2	D3B2-M1808P-O3S2	3
DC 3 wire 10-55v PNP N.C.	D3B1-M1808P-C3A2	D3B2-M1816P-C3A2	4	D3B1-M1808P-C3S2	D3B2-M1816P-C3S2	4
DC 3 wire 5-36V PNP N.C.	D2B1-M1808N-O3A2	D2B2-M1816N-O3A2	1	D2B1-M1808N-O3S2	D2B2-M1816N-O3S2	1
DC 3 wire 5-36V PNP N.O.	D2B1-M1808N-C3A2	D2B2-M1816N-C3A2	2	D2B1-M1808N-C3S2	D2B2-M1816N-C3S2	2
DC 3 wire 5-36V NPN N.C.	D2B1-M1808P-O3A2	D2B2-M1816P-O3A2	3	D2B1-M1808P-O3S2	D2B2-M1816P-O3S2	3
DC 3 wire 5-36V NPN N.O.	D2B1-M1808P-C3A2	D2B2-M1816P-C3A2	4	D2B1-M1808P-C3S2	D2B2-M1816P-C3S2	4
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)	D2B1-M1808P-S4A2	D2B2-M1816P-S4A2	6	D2B1-M1808P-S4S2	D2B2-M1816P-S4S2	6
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)	D2B1-M1808N-S4A2	D2B2-M1816N-S4A2	5	D2B1-M1808N-S4S2	D2B2-M1816N-S4S2	5
Wiring diagram number						
Dimensions (unit: mm)						
Cable 2M (PVC)	5.8φ3x0.15 or 5.8φ4x0.15			4φ3x.0.34 or 4φ4x0.34		
Weight	approx.153g / approx.144g			approx.132g / approx.134g		

Subject to modifications without notice

Tel: +86-755-2646 7962

Fax: +86-755-2646 7925

MSN: dfan852@hotmail.com

Web: www.mountiger.com

E-mail: sales@mountiger.com

QQ: 873764592


Sensing the future