





DC INDUCTIVE PROXIMITY SWITCH(M30)

Diameter	M30		M30		
Shielded/non-Shielded	Shielded/ Non-Shielded		Shielded/ Non-Shielded		
Switching Distance Sn mm	22mm / 40mm		22mm / 40mm		
Housing Material	Nickel plated brass		Nickel plated brass		
With LED/Without LED	With LED		With LED		
Picture					
Operating Voltage	10-30VDC		10-30VDC		
Ripple	<10%		<10%		
No Load Current	<10mA		<10mA		
Max. Load Current	200mA		200mA		
Leakge Current	<0.01mA		<0.01mA		
Voltage Drop	<2.0V		<2.0V		
Switching Frequency	300HZ / 100HZ		300HZ / 100HZ		
Response Time	0.5ms/0.5ms 1ms / 1ms		0.5ms/0.5ms 1ms / 1ms		
Switching Hysteresis	<15%~20%(Sr)		<15%~20%(Sr)		
Repeat Accuracy	<1.0%(Sr)		<1.0%(Sr)		
Protection Category	IP67		IP67		
Operating Temperature	-25 °C - +70 °C		-25 °C - +70 °C		
Temperature Drift	<10%(Sr)		<10%(Sr)		
Short Circuit Protection	YES		YES		
Overload Trip Point	220MA		220MA		
Material Active Face	PBT		PBT		
DC 3 wire 10-30V NPN N.O.	D1B1-M3022N-O3A2	∣ D1B2-M3040N-O3A2	1	D1B1-M3022N-O3S2 ∣ D1B2-M3040N-O3S2	1
DC 3 wire 10-30V NPN N.C.	D1B1-M3022N-C3A2	∣ D1B2-M3040N-C3A2	2	D1B1-M3022N-C3S2 ∣ D1B2-M3040N-C3S2	2
DC 3 wire 10-30V PNP N.O.	D1B1-M3022P-O3A2	∣ D1B2-M3040P-O3A2	3	D1B1-M3022P-O3S2 ∣ D1B2-M3040P-O3S2	3
DC 3 wire 10-30V PNP N.C.	D1B1-M3022P-C3A2	∣ D1B2-M3040P-C3A2	4	D1B1-M3022P-C3S2 ∣ D1B2-M3040P-C3S2	4
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)	-			-	
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)	-			-	
DC 2 wire 10-60V N.O.	-			-	
DC 2 wire 10-60V N.C.	-			-	
DC 3 wire 10-55v NPN N.O.	-			-	
DC 3 wire 10-55v NPN N.C.	-			-	
DC 3 wire 10-55v PNP N.O.	-			-	
DC 3 wire 10-55v PNP N.C.	-			-	
DC 3 wire 5-36V PNP N.C.	-			-	
DC 3 wire 5-36V PNP N.O.	-			-	
DC 3 wire 5-36V NPN N.C.	-			-	
DC 3 wire 5-36V NPN N.O.	-			-	
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)	-			-	
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)	-			-	
Wiring diagram number	↗			↗	
Dimensions (unit: mm)					
Cable 2M (PVC)	5.8φ3x0.5or 5.8φ4x0.5		5.8φ3x0.5or 5.8φ4x0.5		
Weight	approx.217g / approx.207 g		approx.180g / approx.182 g		

Subject to modifications without notice

Tel: +86-755-2646 7962

Fax: +86-755-2646 7925

MSN: dfan852@hotmail.com

Web: www.mountiger.com

E-mail: sales@mountiger.com

QQ: 873764592



Mountiger
 Sensing the future