









DC INDUCTIVE PROXIMITY SWITCH 5 WAY ROTATABLE SENSING HEAD(Q40)

Diameter	Q40		Q40	
Shielded/non-Shielded	Shielded		Non-Shielded	
Switching Distance Sn mm	15mm		20mm	
Housing Material	PBT RESIN		PBT RESIN	
With LED/Without LED	With LED		With LED	
Picture	 		 	
Operating Voltage	10-30VDC / 5-36VDC / 10-55VDC		10-30VDC / 10-55VDC / 10-60VDC	
Ripple	<10%		<10%	
No Load Current	<10mA		<10mA	
Max. Load Current	200mA		200mA	
Leakge Current	<0.01mA		<0.01mA	
Voltage Drop	< 1.5V		< 1.5V	
Switching Frequency	100HZ		100HZ	
Response Time	1ms/1ms		1ms/1ms	
Switching Hysteresis	<15%(Sr)		<15%(Sr)	
Repeat Accuracy	<1.0%(Sr)		<1.0%(Sr)	
Protection Category	IP67		IP67	
Operating Temperature	-25 °C - +70 °C		-25 °C - +70 °C	
Temperature Drift	<10%(Sr)		<10%(Sr)	
Short Circuit Protection	YES		YES	
Overload Trip Point	220MA		220MA	
Material Active Face	PBT		PBT	
DC 3 wire 10-30V NPN N.O.	D1P1-Q4015N-O3A	1	D1P2-Q4020N-O3A	1
DC 3 wire 10-30V NPN N.C.	D1P1-Q4015N-C3A	2	D1P2-Q4020N-C3A	2
DC 3 wire 10-30V PNP N.O.	D1P1-Q4015P-O3A	3	D1P2-Q4020P-O3A	3
DC 3 wire 10-30V PNP N.C.	D1P1-Q4015P-C3A	4	D1P2-Q4020P-C3A	4
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)	D1P1-Q4015P-S4A	6	D1P2-Q4020P-S4A	6
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)	D1P1-Q4015N-S4A	5	D1P2-Q4020N-S4A	5
DC 2 wire 10-60V N.O.	D4P1-Q4015C-O2A	7	D4P2-Q4020C-O2A	7
DC 2 wire 10-60V N.C.	D4P1-Q4015C-C2A	8	D4P2-Q4020C-C2A	8
DC 3 wire 10-55v NPN N.O.	D3P1-Q4015N-O3A	1	D3P2-Q4020N-O3A	1
DC 3 wire 10-55v NPN N.C.	D3P1-Q4015N-C3A	2	D3P2-Q4020N-C3A	2
DC 3 wire 10-55v PNP N.O.	D3P1-Q4015P-O3A	3	D3P2-Q4020N-O3A	3
DC 3 wire 10-55v PNP N.C.	D3P1-Q4015P-C3A	4	D3P2-Q4020N-C3A	4
DC 3 wire 5-36V PNP N.C.	-		-	
DC 3 wire 5-36V PNP N.O.	-		-	
DC 3 wire 5-36V NPN N.C.	-		-	
DC 3 wire 5-36V NPN N.O.	-		-	
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)	-		-	
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)	-		-	
Wiring diagram number				
Dimensions (unit: mm)				
Cable 2M (PVC)	-		-	
Weight	approx.262g		approx.262g	

Subject to modifications without notice

Tel: +86-755-2646 7962

Fax: +86-755-2646 7925

MSN: dfan852@hotmail.com

Web: www.mountiger.com

E-mail: sales@mountiger.com

QQ: 873764592

