









# DC INDUCTIVE PROXIMITY SWITCH 5 WAY ROTATABLE SENSING HEAD(Q40)

Diameter	Q40		Q40	
Shielded/non-Shielded	Shielded		Non-Shielded	
Switching Distance Sn mm	15mm		20mm	
Housing Material	PBT RESIN		PBT RESIN	
With LED/Without LED	With LED		With LED	
Picture	 		 	
Operating Voltage	10-30VDC / 5-36VDC / 10-55VDC		10-30VDC / 10-55VDC / 10-60VDC	
Ripple	<10%		<10%	
No Load Current	<10mA		<10mA	
Max. Load Current	200mA		200mA	
Leakge Current	<0.01mA		<0.01mA	
Voltage Drop	< 1.5V		< 1.5V	
Switching Frequency	100HZ		100HZ	
Response Time	1ms/1ms		1ms/1ms	
Switching Hysteresis	<15%(Sr)		<15%(Sr)	
Repeat Accuracy	<1.0%(Sr)		<1.0%(Sr)	
Protection Category	IP67		IP67	
Operating Temperature	-25 °C - +70 °C		-25 °C - +70 °C	
Temperature Drift	<10%(Sr)		<10%(Sr)	
Short Circuit Protection	YES		YES	
Overload Trip Point	220MA		220MA	
Material Active Face	PBT		PBT	
DC 3 wire 10-30V NPN N.O.	D1P1-Q4015N-OEA4	31	D1P2-Q4020N-OEA4	31
DC 3 wire 10-30V NPN N.C.	D1P1-Q4015N-CEA4	32	D1P2-Q4020N-CEA4	32
DC 3 wire 10-30V PNP N.O.	D1P1-Q4015P-OEA4	33	D1P2-Q4020P-OEA4	33
DC 3 wire 10-30V PNP N.C.	D1P1-Q4015P-CEA4	34	D1P2-Q4020P-CEA4	34
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)	D1P1-Q4015P-SEA4	36	D1P2-Q4020P-SEA4	36
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)	D1P1-Q4015N-SEA4	35	D1P2-Q4020N-SEA4	35
DC 2 wire 10-60V N.O.	D4P1-Q4015C-OEA4	37	D4P2-Q4020C-OEA4	37
DC 2 wire 10-60V N.C.	D4P1-Q4015C-CEA4	38	D4P2-Q4020C-CEA4	38
DC 3 wire 10-55v NPN N.O.	D3P1-Q4015N-OEA4	31	D3P2-Q4020N-OEA4	31
DC 3 wire 10-55v NPN N.C.	D3P1-Q4015N-CEA4	32	D3P2-Q4020N-CEA4	32
DC 3 wire 10-55v PNP N.O.	D3P1-Q4015P-OEA4	33	D3P2-Q4020P-OEA4	33
DC 3 wire 10-55v PNP N.C.	D3P1-Q4015P-CEA4	34	D3P2-Q4020P-CEA4	34
DC 3 wire 5-36V PNP N.C.	-		-	
DC 3 wire 5-36V PNP N.O.	-		-	
DC 3 wire 5-36V NPN N.C.	-		-	
DC 3 wire 5-36V NPN N.O.	-		-	
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)	-		-	
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)	-		-	
Wiring diagram number				
Dimensions (unit: mm)				
Cable 2M (PVC)	-		-	
Weight	approx.290g		approx.290g	

Subject to modifications without notice

Tel: +86-755-2646 7962

Fax: +86-755-2646 7925

MSN: dfan852@hotmail.com

Web: www.mountiger.com

E-mail: sales@mountiger.com

QQ: 873764592

